



DRILLING FLUID APPLICATION GUIDELINES

Based on 300 Gallon Make-up System

Use approximately 1/3 pound of soda ash to bring water to a pH of 8 to 9 if needed.

SOIL TYPE Marsh Funnel Viscosity	SANDY Formation 55-65 Sec/Qt	CLAY Formation 40-45 Sec/Qt	GENERAL Formations 45-55 Sec/Qt
EXTRA HIGH YIELD™ GEL	2 – 2½ Bags ±	1½ Bags ± (NA)	1 ½ - 2 Bags ±
EXTRA HIGH YIELD™ GEL & UNI-DRILL®	1 - 2 Bags ± 2 ± Qts. UNI-DRILL®	1 Bag ± 3 ± Qts. UNI-DRILL®	1 - 1½ Bags ± 3 - 4 Qts. UNI-DRILL®
WYO-VIS®	3½ - 5 Qts. ± (NA)	1½ - 2½ Qts. ±	3 – 3½ Qts. ±
BORZAN®	13½ lbs. ±	10½ lbs. ±	12 lbs. ±
KWIS-VIS™ D	1 - 1½ lbs. ± (NA)	¾ - 1¼ lbs. ±	¾ - 1½ lbs. ±
(NA) -“Not Applicable”			