



# DRILLING FLUID APPLICATION GUIDELINES

## Based on 300 Gallon Make-up System

Use approximately 1/3 pound of Soda Ash to bring water to a pH of 8 to 9 if needed.

<b>SOIL TYPE</b> Marsh Funnel Viscosity	<b>SANDY</b> Formation 55-65 Sec/Qt	<b>CLAY</b> Formation 40-45 Sec/Qt	<b>GENERAL</b> Formations 45-55 Sec/Qt
<b>EXTRA HIGH YIELD™ GEL</b>	2 – 2½ Bags ±	1½ Bags ± (NA)	1 ½ - 2 Bags ±
<b>EXTRA HIGH YIELD™ GEL</b> & <b>UNI-DRILL®</b>	1 - 2 Bags ± 2 ± Qts. <b>UNI-DRILL®</b>	1 Bag ± 3 ± Qts. <b>UNI-DRILL®</b>	1 - 1½ Bags ± 3 - 4 Qts. <b>UNI-DRILL®</b>
<b>WYO-VIS® HP</b>	3½ - 5 Qts. ± (NA)	1½ - 2½ Qts. ±	3 – 3½ Qts. ±
<b>BORZAN®</b>	13½ lbs. ±	10½ lbs. ±	12 lbs. ±
<b>KWIS-VIS™ D</b>	1 - 1½ lbs. ± (NA)	¾ - 1¼ lbs. ±	¾ - 1½ lbs. ±
(NA) - "Not Applicable"			