

## **TECHNICAL INFORMATION**



## EXTRA HIGH YIELD™

**Description: EXTRA HIGH YIELD<sup>TN</sup>** is a high viscosity bentonite for drilling, boring and tunneling applications as

well as slurry wall construction.

**Typical Characteristics:** Barrel Yield (Bbl/ton):  $210 \pm 10$ 

Bulk Density (lbs./ft<sup>3</sup>):  $52 \pm 3$ Cation Exchange Capacity 70 - 90

(meq(100gm):

Color: Light Grey to Tan

Fluid Loss (cc):  $25 \pm 2$ Moisture Content (%): 5 - 12pH:  $9.1 \pm 0.4$ Sieve Analysis >79

(% Passing #200 Sieve):

Specific Gravity: $2.55 \pm 0.1$ Wet Screen Analysis $3.0 \pm 0.5$ 

(Residue on #200 Sieve):

Typical Chemical Analysis:	%	
SiO₂	60.34	
$Al_2O_3$	19.28	
Fe <sub>2</sub> O <sub>3</sub>	3.48	
Na₂O	2.34	
TiO₂	.22	
CaO	.38	
MgO	1.67	
K <sub>2</sub> O	.10	
H₂O	7.75	
Other	.07	
L.O.I.	4.37	

E.P.A Toxicity Analysis:	E.P.A Standard (ppm)	Typical Analysis (ppm)
Arsenic	5.0	<0.1
Barium	100.0	0.5
Cadmium	1.0	<0.05
Chromium	5.0	<0.1
Lead	5.0	<0.1
Mercury	0.2	<0.02
Selenium	1.0	<0.05
Silver	5.0	<0.1

Rev 3/17