



VC-55™



Product Information

Description

VC-55™ is a unique product designed to aid in most solids vacuuming operations. In pot holing, this additive significantly reduces the amount of water required by assisting in the lifting of spoils. **VC-55™** lubricates both the hoses and solids by covering them with a low-friction coating that facilitates easy transport into the holding tank. This coating also aids in dumping, as the spoils are easily expelled from the tank with little or no bridging. **VC-55™** is a real time-saver, allowing for more effective vacuuming and disposal, by significantly reducing turn-around times for off-loading. Operators spend less time cleaning and pressure washing the hoses and tank. **VC-55™** is a viscous liquid that remains pourable to 10°F. It is environmentally friendly and non-toxic.

Characteristics

- Makes pot-holing easy in sticky clays
- Reduces spoils adhering to tank walls and corners
- Speeds dumping since spoils don't stick to tank walls
- Reduces maintenance
- Limits the wash-out of hoses and tank
- Vac and dump turn-around time is reduced by as much as 65%

Application

Shake the **VC-55™** container well before use. Add 8 to 16 ounces per 200 to 250 gallon water tank. Vigorously agitate with the wash-wand to completely disperse the **VC-55** into the water. Proceed as normal with the pot-holing operation.

Packaging

VC-55™ is packaged in 1 quart plastic bottles, 12 quarts per case.