



ENVIROPLUG® COATED TABLETS



Product Information

Description

ENVIROPLUG® COATED TABLETS allow for deeper, more predictable placement of tablets. The coated exterior prevents the “sticky rind” from forming once water contacts the bentonite. Because hydration time is retarded, the **ENVIROPLUG®** COATED TABLETS can be placed through a tremie line assisting in predictable placement. They make a high density, low permeability buffer seal between sand packs and cement or bentonite grouts.

Characteristics

- Clean, dust-free and easy to handle
- Non-toxic, non-polluting
- Permeability 1 x 10⁻⁸ to 1 x 10⁻⁹ cm/sec
- Make-Up Sodium Montmorillonite
- Bulk Density 75 to 80 pounds per cubic foot
- Color Gray to grayish tan

Description

ENVIROPLUG® COATED TABLETS allow for deeper, more predictable placement of tablets. The coated exterior prevents the “sticky rind” from forming once water contacts the bentonite. Because hydration time is retarded, the COATED **ENVIROPLUG®** TABLETS can be placed through a tremie line assisting in predictable placement. They make a high density, low permeability buffer seal between sand packs and cement or bentonite grouts.

Application

Once in place, the **ENVIROPLUG®** COATED TABLETS should be allowed to hydrate for 4 to 6 hours before a bentonite grout medium is installed. If cementitious grout is used allow a minimum of 6 hours hydration time. They can be used in conjunction with steel or PVC casing and generate no heat while hydrating.

Hole Diameter	CASING SIZE		
	2 Inch	4 Inch	6 Inch
4 inch	0.4 gal/ft	NA	NA
6 inch	1.3 gal/ft	0.7 gal/ft	NA
8 inch	2.3 gal/ft	1.8 gal/ft	0.8 gal/ft
10 inch	3.8 gal/ft	3.2 gal/ft	2.3 gal/ft

Packaging

ENVIROPLUG® coated TABLETS are packaged in 50 pound plastic pails.