



# PRODUCT USAGE AND CROSS REFERENCE

(The reference is for application and function only and does not COMPARE usage rates of competitive products.)

| WYO-BEN                     | BAROID                    | CETCO                          | M-I SWACO                 | DESCRIPTION                                      |
|-----------------------------|---------------------------|--------------------------------|---------------------------|--|
| AIR FOAM®                   | Quik-Foam                 | --                             | --                        | Foaming agent for air drilling                   |
| BIG HORN 30                 | Baroid Granular Bentonite | C/S Granular                   | --                        | Casing Seal                                      |
| BORZAN®                     | No-Sag                    | Suspend-It                     | Duo-Vis/Super-Vis         | Biopolymer HDD Drilling Fluid                    |
| CLAYMASTER®                 | --                        | Clay Cutter                    | Kla-Guard                 | Liquid clay inhibitor                            |
| DRILL-X™ HP                 | Con Det                   | Drill Terge                    | Platinum D-D              | Drilling detergent                               |
| DRIL-SOL™                   | --                        | --                             | --                        | Clay stabilizer mud conditioner                  |
| DRIL-TROL™ QD               | Quik-Trol                 | Rel-Pac                        | Platinum Pac              | Dry polymer viscosifier / fluid loss control     |
| ENVIROPLUG® GROUT           | Aquaguard                 | PureGold Grout                 | Smooth Grout 30           | 30% solids grout                                 |
| ENVIROPLUG® MEDIUM & COARSE | HolePlug 3/8 & 3/4        | PureGold Medium & Cetco Coarse | Kwik-Plug Medium & Coarse | Casing seal and abandonment                      |
| ENVIROPLUG® NO. 16          | BenSeal                   | Crumbles                       | Kwik-Plug Micro           | Casing seal                                      |
| ENVIROPLUG® NO. 20          | BenSeal                   | Crumbles                       | Kwik-Plug Micro           | Casing seal                                      |
| ENVIROPLUG® NO. 8           | Casing Seal               | Crumbles                       | Kwik-Plug Fine            | Casing seal                                      |
| ENVIROPLUG® TABLETS         | Pellets                   | Cetco Tablets                  | Kwik-Plug Pellets         | Casing seal and abandonment                      |
| EXTRA HIGH YIELD™           | Quik-Gel                  | Super Gel X                    | Max Gel                   | 220 barrel yield bentonite                       |
| FLOWMASTER® LV              | Quik-Trol LV              | Rel-Pak Xtra-Low               | Platinum Pac UL           | Dry polymer / low viscosity / fluid loss control |
| G-150 GUAR                  | --                        | Variflo QD                     | Guar Gum                  | Guar gum viscosifier                             |
| GROUT-WELL®                 | --                        | Cetco Grout                    | Smooth Grout 20           | 20% solids grout                                 |
| GROUT-WELL® DF              | Quik-Grout                | Cetco Granular Grout           | Gopher Grout              | 20% solids grout, low dust                       |
| HYDROGEL®                   | Aquagel                   | Premium Gel                    | MI-Gel                    | A.P.I. 13A, Sec. 9 bentonite                     |
| HYDROGEL® PLUS              | --                        | --                             | --                        | 200 barrel yield bentonite                       |
| KWIK-VIS™ "D"**             | Poly-Bore                 | Shore Pac                      | Poly-Plus EHV             | Dry polymer viscosifier                          |
| MICRO-GEL™                  | Tunnel-Gel Plus           | --                             | --                        | Tunnel slurry, lubricating fluid                 |
| MTA-1™                      | --                        | --                             | --                        | Tunnel lubricating fluid additive                |
| PLUGZ-IT™ /Max              | Diamond Seal              | Macro-Fill                     | Polyswell                 | Loss circulation additive                        |
| PowerTEC                    | --                        | Cetco TC Booster               | --                        | Graphite additive enhances thermal conductivity  |
| SOLIDIBOND™ 1.1 & 2.2       | --                        | SlurryBond                     |                           | Highly efficient fluid solidification agent      |
| SW-101™                     | Tunnel-Gel SW             | --                             | --                        | Bentonite based sea water viscosifier            |
| TD-16®                      | EZ-Seal                   | --                             | --                        | Grouting and abandonment                         |
| THERM-EX GROUT™             | Barotherm Gold            | Geo Thermal Grout              | Smooth Grout Thermal      | Thermally enhanced grout .93 to 1.2 Btu/hr-ft-°F |
| THINZ-IT®                   | Aqua-Clear PFD            | Super Thin                     | Ringfree                  | Liquid mud thinner                               |
| TRU-BORE®**                 | Bore-Gel                  | Hydraul-Ez                     | Maxbore HDD               | Premium HDD bentonite                            |
| UNI-DRILL®                  | Liqui-Trol                | Super Pac                      | --                        | Liquid polymer viscosifier/fluid loss control    |
| VC-55™                      | --                        | --                             | --                        | Vac. system lubricant                            |
| WYO-DEFOAMER™               | Bara-Defoam 500           | Cetco Defoamer                 | --                        | Foam breaker                                     |
| WYO-FOAMER™ 800             | AQF-2                     | VersaFoam Plus                 | Platinum Foam Plus        | Premium all-purpose foam                         |
| WYO-LUBE RR                 | Dinomul 2                 | Cetco C-Lube                   | Rod Ease                  | Liquid Lubricant                                 |
| WYO-VIS® HP                 | E-Z Mud                   | Insta-Vis Plus                 | Poly-Plus                 | Liquid viscosifier                               |
| WYO-VIS® LVP                | E-Z Mud Gold              | Insta-Vis Low Viscosity        | Poly-Plus LV              | Low viscosity shale inhibitor                    |

\* Usage applies only to Wyo-Ben products.    \*\* Application rates for competitive products are significantly higher.

(11/2019)



# PRODUCT APPLICATION GUIDELINES

*Based on 100 Gallon (378.54ltr) Make-up System  
Use approximately 1.6oz of soda ash to bring water to a pH of 8 to 9*

|                                 | Cobble   | Sand & Gravel       | Sandy Clay             | Clay                   | Reactive Clay      |
|---------------------------------|--|---------------------|------------------------|------------------------|--------------------|
| <b>Marsh Funnel Viscosity</b>   | 60-65 Sec/Qt.  | 50-60 Sec/Qt        | 45-50 Sec/Qt           | 40-45 Sec/Qt           | 35-40 Sec/Qt       |
| Borzan/Borzan D                 | 5lbs   | 4lbs                | 3lbs                   | NA                     | NA                 |
| Claymaster                      | 13oz – 16oz Depending on Sensativity of the Formation                  |                     |                        |                        |                    |
| Dril-Sol                        | 1gal – 1.3gals Depending on Sensativity of the Formation               |                     |                        |                        |                    |
| Dril-Trol QD                    | .25lb – 1lb Depending on Sensativity of the Formation                  |                     |                        |                        |                    |
| Drill-X HP                      | .7qt – 1.3qts Depending on Sensativity of the Formation                |                     |                        |                        |                    |
| Extra High Yield                | ± 40lbs  | ± 30lbs             | ± 27lbs                | ± 23lbs                | ± 20lbs            |
| Extra High Yield & Claymaster   | NA   | NA                  | ± 27lbs & .5qt-1qt     | ± 23lbs & 1qt-1.5qts   | ± 20lbs & 2qts     |
| Extra High Yield & Dril-Trol QD | ± 30lbs & ± 4oz  | ± 25lbs & ± 6.5oz   | ± 20lbs & ± 9.5oz      | ± 17.5lbs & ± 13oz     | ± 215lbs & ± 1lb   |
| Extra High Yield & Uni-Drill    | ± 30lbs & ± 11fl oz  | ± 25lbs & ± 19fl oz | ± 20lbs & ± 26fl oz    | ± 17.5lbs & ± 1.2qts   | ± 15lbs & ± 1.5qts |
| Extra High Yield & Wyo-Vis LVP  | ± 30lbs & ± 5oz  | ± 25lbs & ± 7oz     | ± 20lbs & ± 11oz       | ± 17.5lbs & ± 1lb      | ± 15lbs & ± 1.5lbs |
| Hydrogel Plus & Uni-Drill       | ± 32lbs & ± 14fl oz  | ± 27lbs & ± 25fl oz | ± 22lbs & ± 1qts       | ± 19lbs & ± 1.3qts     | ± 17lbs & ± 1.6qts |
| Kwik-Vis D                      | NA   | NA                  | ± 1.25lbs              | ± 12oz                 | ± 8oz              |
| Plugz-It Max                    | Pill – 30lbs/100gal, or Trickle at Suction as Needed                   |                     |                        |                        |                    |
| SW-101                          | 70lbs – 100lbs   |                     |                        |                        |                    |
| Thinz-It                        | 1pt – 2pts for Mud Thinning, 2gal – 5gal Slug at Screen for Completion |                     |                        |                        |                    |
| Tru-Bore                        | ± 30lbs  | ± 25 lbs            | ± 22.5lbs              | ± 18lbs                | ± 12lbs            |
| Tru-Bore & Claymaster           | NA   | NA                  | ± 22.5lbs & .5qt – 1qt | ± 18lbs & 1qt – 1.5qts | ± 12lbs & 2qts     |
| Tru-Bore & Dril-Trol QD         | ± 25lbs & ± 4oz  | ± 22.5lbs & ± 6.4oz | ± 18lbs & ± 9.5oz      | ± 12lbs & ± 13oz       | ± 10lbs & ± 1lb    |
| Tru-Bore & Uni-Drill            | ± 25lbs & ± 11oz   | ± 22.5lbs & ± 19oz  | ± 18lbs & ± 26oz       | ± 12lbs & ± 1.2qts     | ± 10lbs & ± 1.5qts |
| Tru-Bore & Wyo-Vis LVP          | ± 30lbs & ± 5oz  | ± 22.5lbs & ± 7oz   | ± 18lbs & ± 11oz       | ± 12lbs & ± 1lb        | ± 10lbs & ± 1.5lbs |
| Wyo-Lube RR                     | 0.5% - 2% Addition by Volume as Needed                                 |                     |                        |                        |                    |
| Wyo-Vis HP                      | NA   | NA                  | ± 1.5qts               | ± 1qt                  | ± 1qt              |
| Wyo-Vis LVP                     | NA   | NA                  | ± 2.5lbs               | ± 2lbs                 | ± 2lbs             |

(11/2019)