



DRIL-TROL™ QD



Certified to
NSF/ANSI/CAN 60

Product Information

Description

DRIL-TROL™ QD is a unique **quickly dispersible**, highly concentrated proprietary dry polymer designed for use in vertical and horizontal directional drilling operations. It conditions drilling fluids to control fluid loss, prevent formation clays from swelling, and will keep tools clean by preventing bit balling. **DRIL-TROL™ QD** also aids in the effective operation of solids control equipment by dropping silts and sands from the fluid. It is environmentally safe and non-fermenting. Unlike most polymers, **DRIL-TROL™ QD** is tolerant to brackish and harsh water conditions.

Characteristics

- Safe: Non-polluting, Non-fermenting
- Controls fluid loss
- Coats and inhibits clays
- Builds viscosity
- Quick dispersing
- Performs in saline environments
- Reduces friction, torque and drag

Application

For 500 gallon make-up water, add approximately 1/4 pound of soda ash to bring water a pH of 8 to 9. In any fluid, always add bentonite products before adding the polymer.

CLAY 40 – 45 sec/qt	
EXTRA HIGH YIELD™ & DRIL-TROL™ QD	1 1/2 bag & 4 lbs. DRIL-TROL™ QD
TRU-BORE® & DRIL-TROL™ QD	1 bag & 3 lbs. DRIL-TROL™ QD
SAND 55 – 65 sec/qt	
EXTRA HIGH YIELD™ & DRIL-TROL™ QD	2 3/4 bags & 2 lbs. DRIL-TROL™ QD
TRU-BORE® & DRIL-TROL™ QD	1 1/2 bags & 1 lb. DRIL-TROL™ QD
UNKNOWN OR MEDIUM SOILS 45 – 55 sec/qt	
EXTRA HIGH YIELD™ & DRIL-TROL™ QD	2 1/4 bags & 3 lbs. DRIL-TROL™ QD
TRU-BORE® & DRIL-TROL™ QD	1 bag & 3 lbs. DRIL-TROL™ QD

Packaging

DRIL-TROL™ QD is available in resealable 12 lb. plastic jugs – 3 jugs per case and 25 lb pail.

4041/201302

WYO-BEN, INC., Billings, Montana

800.548.7055

406.652.6351

www.wyoben.com

The information and data made herein are believed to be accurate. As Wyo-Ben, Inc. has no control over use or application of this product, it is sold without warranty or guarantee of results.