



TECHNICAL INFORMATION



GROUT-WELL®

Description: GROUT-WELL® is a specially formulated, powdered, 20% solids bentonite product for use in sealing and abandonment of water wells, monitor wells and other geotechnical applications.

Typical Characteristics:	Bulk Density (lbs./ft³):	55
	Cation Exchange Capacity (CEC meq(100gm):	70 – 90
	Color:	Light Grey to Tan
	Moisture Content (%):	5 – 12
	Permeability (cm/sec):	1 X 10 ⁻⁸
	pH:	9.1 ± 0.4
	Resistivity (ohm-meters)	2.8
	Sieve Analysis (% Passing #200 Sieve):	>79
	Specific Gravity:	2.55 ± 0.1
	Thermal Conductivity (Btu/hr-ft-°F):	0.42
	Wet Screen Analysis (Residue on #200 Sieve):	3.0 ± 0.5

Typical Chemical Analysis:	%
SiO ₂	60.34
Al ₂ O ₃	19.28
Fe ₂ O ₃	3.48
Na ₂ O	2.34
TiO ₂	.22
CaO	.38
MgO	1.67
K ₂ O	.10
H ₂ O	7.75
Other	.07
L.O.I.	4.37

E.P.A Toxicity Analysis:	E.P.A Standard (ppm)	Typical Analysis (ppm)
Arsenic	5.0	<0.1
Barium	100.0	0.5
Cadmium	1.0	<0.05
Chromium	5.0	<0.1
Lead	5.0	<0.1
Mercury	0.2	<0.02
Selenium	1.0	<0.05
Silver	5.0	<0.1

Rev 10/23