



TECHNICAL INFORMATION



PLUGZ-IT™ MAX

Description: **PLUGZ-IT™ MAX** is a specially sized bentonite polymer blend for use in lost circulation applications.

Typical Characteristics:	Bulk Density (lbs./ft³):	63 ± 3
	Color:	Light Grey to Tan
	Moisture Content:	6% - 10%
	pH:	9.1 ± 0.4
	Specific Gravity:	2.55 ± 0.1

Typical Sieve Analysis:	Sieve Size	% Retained
	#4	0.23
	#8	41.18
	#12	40.63
	#20	17.42
	Pan	0.48

Typical Chemical Analysis:	%
SiO ₂	60.34
Al ₂ O ₃	19.28
Fe ₂ O ₃	3.48
Na ₂ O	2.34
TiO ₂	.22
CaO	.38
MgO	1.67
K ₂ O	.10
H ₂ O	7.75
Other	.07
L.O.I.	4.37

E.P.A Toxicity Analysis:	E.P.A Standard (ppm)	Typical Analysis (ppm)
Arsenic	5.0	<0.1
Barium	100.0	0.5
Cadmium	1.0	<0.05
Chromium	5.0	<0.1
Lead	5.0	<0.1
Mercury	0.2	<0.02
Selenium	1.0	<0.05
Silver	5.0	<0.1

Rev 10/23