



TRU-BORE®



Certified to NSF/ANSI/CAN 60

Product Information

Description

TRU-BORE® is a highly concentrated bentonite-based drilling fluid designed for difficult drilling operations in both vertical and horizontal borings. It is an extremely effective high performance viscosifier for horizontal drilling applications to maintain borehole integrity during pullback. It is non-toxic and environmentally safe. Its fast-hydrating formula allows contractors to mix fast and build viscosity quickly. **TRU-BORE®** stabilizes formations ranging from moderate clay soils to high concentrations of sand. By forming a thin tough filter cake, fluid loss to areas around the borehole is reduced. These factors, coupled with excellent gel strength values make **TRU-BORE®** the best risk management tool available today.

Characteristics

- Barrel Yield: 240 - 250
- Fluid Loss: 12 – cc.
- Mesh: 80% ± 2 passing 200 mesh
- PH 8.1 ± .2
- Moisture: 8% ± 1.5

Application

For every 100 gallons of make-up water, adding 15 to 25 pounds of **TRU-BORE®** will yield a viscosity of approximately 45 seconds on a Marsh Funnel. At a rate of 27 pounds per 100 gallons, viscosity can climb to 60 seconds.

CLAY
1½ bags for viscosity of 32-35 seconds, then add UNI-DRILL® liquid polymer to reach a viscosity of 42-45 seconds. (The addition of UNI-DRILL® keeps the clays from thickening the mud system even more.)
SAND
2¼ - 3 bags for viscosity of 55 ± seconds
UNKNOWN OR MEDIUM SOILS
1½ - 3 bags for viscosity of 45 seconds

Packaging

TRU-BORE® is packaged in 50 pound multi-walled paper bags, palletized 60 bags per pallet and shrink-wrapped.

4375/201302